

**OUTDOOR DECORATIVE WALL LIGHT WAVE IP65 310LM 7W 3000K UP/DOWN LIGHT DARK GREY INTEGRAL**

ILDEA011



Discover Integral's new outdoor range. Light up the exterior of your home with these compact, stylish and contemporary LED luminaires. Weatherproof and hard-wearing, this range is designed to last against the elements while bringing a designer look to your surroundings. The Wave's linear up/down design brings a modern feel to your outdoor areas. Constructed with a polycarbonate diffuser so you are left with a soft, even glow.

**Details**

<b>Quick Order Code:</b>	296172
<b>Barcode:</b>	5055788232445
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Wall Light
<b>Product Type:</b>	Outdoor
<b>Market Segment:</b>	Residential Outdoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	230
<b>Product Depth (mm):</b>	58
<b>Product Width (mm):</b>	72
<b>Product Weight (g):</b>	400
<b>Optic:</b>	Opal Polycarbonate diffuser
<b>Material:</b>	Die cast aluminium body with powder coated finish
<b>Luminaire Fixing:</b>	Wall Mounted
<b>Placement / Application:</b>	Outdoor, General Lighting

**Electrical Data**

<b>Power Consumption (w):</b>	7
<b>Power Factor:</b>	0.8
<b>Amperage (mA):</b>	300
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC

EN: EN-60598  
LVD Certified: Yes

## Light Data

Luminous Flux in Lumens (lm): 310  
Luminous efficacy (lm/W): 44  
Correlated Colour Temperature (CCT) (K): 3000  
Colour Temperature Name: Warm White  
Colour Rendering Index (CRI): 80  
Frequency Range (Hz): 50/60  
Instant on (Less than 1 second): Yes  
LED Type: Surface mounted device (SMD)  
Lifetime (hours): 25000  
Switching Cycles: 12500

## Environment

EN: EN-60598  
LVD Certified: Yes  
CE RoHS: Yes  
New Energy Rating: G  
EU Luminaire: L  
Hg 0% (Mercury Free): Yes  
IP Rating (Ingress Protection): IP65  
Lowest Operating Temperature (°C): -20  
Maximum Operating Temperature (°C): 65



## Packaging

Package Weight (g): 450  
Package Length (mm): 240  
Package Width (mm): 85  
Package Depth (mm): 70

[Portal.integral-led.com](http://Portal.integral-led.com)