

# Solista LX Wall VAD

Part No. **BF440C/F/1**



## Overview

Certified to EN54 Parts 23 (AFNOR) and 13(BSI).

Provides W-2.4-7.5 coverage (switchable to W-2.4-2.5 if required).

10-25mA alarm current depending on setting.

Attractive slim design.

Ultra-bright red LED.

Ideal for use in bedrooms, bathrooms and toilets.

## Technical Specifications

|                                  |  |
|----------------------------------|--|
| Approvals/certifications         | Certified to EN54-23 by AFNOR and EN54-13 by the BSI.  |
| Protocol/compatibility           | Can be used on the conventional sounder circuits of most conventional fire panels including C-TEC's FP, MFP, CFP & EP203. Can also be used on the conventional sounder circuits provided on CTEC's XFP and ZFP addressable panels. |
| Application/operation            | Designed to be wall mounted. Indoor areas only.  |
| VAD category & coverage          | W-2.4-7.5 (switchable to W-2.4-2.5, reducing power consumption by up to 50%).  |
| Flash rate & colour              | 1Hz (switchable to 0.5Hz) / red.   |
| Supply/operating voltage         | 9-60V DC.  |
| Quiescent current                | TBC.   |
| Alarm current                    | 10-25mA dependent on setting.  |
| Product dimensions (mm)          | 93mm diameter x 38mm deep.   |
| Construction & finish            | ABS FR & polycarbonate.  |
| IP Rating                        | IP33C.   |
| Weight                           | 100g.  |
| Operating conditions/temperature | -25°C to +70°C.  |



T 01942 322744    E sales@c-tec.co.uk  
F 01942 829867    W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



T 01942 322744    E sales@c-tec.co.uk  
F 01942 829867    W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom