

DOWNLIGHTS SPECIFICATION SHEET



**COLLINGWOOD
LIGHTING**

01604 495 151
collingwoodlighting.com

/collingwoodlighting

/collingwoodlighting

collingwoodled

GU10 Downlight

Fire-rated fixed IP20 downlight

FEATURES

IP rating	IP20
Tilttable	No
Input	220-240V 50/60Hz

INSTALLATION INFORMATION

Install Connector Type	Push-fit terminal connector
Insulation Coverable	All insulation
Cut Out Size	Ø 65-70mm
Construction Material	Mild steel
Maximum ceiling thickness	40mm
Weight	0.213g
Building regulations	Part B, C, E, P
Ceiling Joist Approvals	Solid timber
Electric Class [1, 2, 3]	1

GUARANTEE / WARRANTY

3 year extended warranty

FEATURES & BENEFITS

Loop-in loop-out connector for ease of installation

30, 60, 90 min fire rating providing additional safety

Acoustic and moisture tested

6-Watt LED or 50-Watt halogen lamp compatible for additional versatility

IP20

White Bezel

WIRING INFORMATION

Cable / Flying Lead	n/a
Cable Required for Connector	Push-fit terminal for: Twin & Earth [6242Y 2x1.5mm ²]
Type of Wiring Required	Parallel

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A	220-240V	N/A	N/A	N/A	N/A	N/A

ACCESSORIES

Collingwood Smart GU10 Lamps	Sold Separately
------------------------------	-----------------

PRODUCT CODES

Product code	Finish	Description
CWFRC001	Matt white	GU10 Fire rated downlight, Fixed, IP20, White
CWFRC002	Brushed steel	GU10 Fire rated downlight, Fixed, IP20, Brushed Steel
CWFRC003	Polished chrome	GU10 Fire rated downlight, Fixed, IP20, Polished Chrome
CWFRC004	Matt white	GU10 Fire rated downlight, Fixed, IP65, White
CWFRC005	Brushed steel	GU10 Fire rated downlight, Fixed, IP65, Brushed Steel
CWFRC006	Polished chrome	GU10 Fire rated downlight, Fixed, IP65, Polished Chrome
CWFRC007	Matt white	GU10 Fire rated downlight, Adjustable, IP20, White
CWFRC008	Brushed steel	GU10 Fire rated downlight, Adjustable, IP20, Brushed Steel
CWFRC009	Polished chrome	GU10 Fire rated downlight, Adjustable, IP20, Polished Chrome

