



express electrical

TYPE YY PVC CONTROL CABLE



APPLICATION

YY Control Cable is used as a control cable on conveyors, assembly and production lines. It is generally used indoors as an interconnecting cable in signal and control equipment.

CABLE STANDARDS

GENERALLY TO BS EN 50525-2-11
VDE 0250

CONSTRUCTION

Conductor: Plain Annealed Stranded Copper Conductors

Insulation: PVC

Sheath: PVC

Sheath Colour: Grey

CHARACTERISTICS

Voltage Rating: 300/500 volts

Temperature Limits:
Static: -20°C to +80°C
Flexing: -5°C to +70°C

Minimum Bending Radius:
As per cable manufacturer datasheet

Core Identification:
2 core - ■ Black with □ white numbers

3 core and above - ■ Black with □ white numbers plus ■ G/Y

Also available with coloured cores as follows:

2 core - ■ Blue ■ Brown

3 core - ■ Blue ■ Brown ■ G/Y

4 core - ■ Brown ■ Black ■ Grey ■ G/Y

5 core - ■ Blue ■ Brown ■ Black ■ Grey ■ G/Y

7 core - ■ Blue ■ Brown ■ Black ■ Grey
□ White ■ Red ■ G/Y

Should not be installed at temperatures below -5°C



express electrical

TYPE YY PVC CONTROL CABLE - DIMENSIONS

CCC CODE	CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NO. OF CORES	WEIGHT (Kg/Km)	OUTSIDE DIAMETER (MM)	GLAND SIZE (MM)
YY2X/75	0.75	24/0.20	2	46	5.60	20/16
YY3X/75	0.75	24/0.20	3	52	5.70	20/16
YY4X/75	0.75	24/0.20	4	64	6.20	20/16
YY5X/75	0.75	24/0.20	5	77	7.00	20/16
YY7X/75	0.75	24/0.20	7	95	7.30	20/16
YY12X/75	0.75	24/0.20	12	155	9.50	20S
YY25X/75	0.75	24/0.20	25	305	13.20	20
YY34X/75	0.75	24/0.20	34	460	16.70	25
YY50X/75	0.75	24/0.20	50	578	18.40	25
YY65X/75	0.75	24/0.20	65	850	23.50	32
YY2X1	1	32/0.20	2	55	6.00	20/16
YY3X1	1	32/0.20	3	66	6.10	20/16
YY4X1	1	32/0.20	4	82	6.70	20/16
YY5X1	1	32/0.20	5	93	7.50	20/16
YY7X1	1	32/0.20	7	121	8.10	20S
YY12X1	1	32/0.20	12	200	11.00	20S
YY18X1	1	32/0.20	18	318	12.70	20
YY25X1	1	32/0.20	25	415	15.50	25
YY34X1	1	32/0.20	34	575	18.30	25
YY41X1	1	32/0.20	41	665	19.00	25
YY50X1	1	32/0.20	50	815	21.30	32
YY65X1	1	32/0.20	65	1055	25.60	32
YY2X1/5	1.5	30/0.25	2	69	6.60	20/16
YY3X1/5	1.5	30/0.25	3	87	7.00	20/16
YY4X1/5	1.5	30/0.25	4	110	7.60	20/16
YY5X1/5	1.5	30/0.25	5	124	8.10	20S
YY7X1/5	1.5	30/0.25	7	176	9.20	20S
YY8X1/5	1.5	30/0.25	8	230	11.20	20
YY10X1/5	1.5	30/0.25	10	265	12.40	20
YY12X1/5	1.5	30/0.25	12	290	13.10	20
YY18X1/5	1.5	30/0.25	18	424	14.80	25
YY25X1/5	1.5	30/0.25	25	565	18.00	25
YY34X1/5	1.5	30/0.25	34	775	21.00	32
YY50X1/5	1.5	30/0.25	50	1095	24.30	32
YY65X1/5	1.5	30/0.25	65	1390	28.80	40
YY2X2/5	2.5	50/0.25	2	106	7.80	20/16
YY3X2/5	2.5	50/0.25	3	126	8.10	20S
YY4X2/5	2.5	50/0.25	4	159	8.90	20S
YY5X2/5	2.5	50/0.25	5	178	9.70	20S
YY7X2/5	2.5	50/0.25	7	272	11.10	20S
YY8X2/5	2.5	50/0.25	8	350	13.50	20
YY12X2/5	2.5	50/0.25	12	403	13.80	20
YY18X2/5	2.5	50/0.25	18	597	17.50	25
YY25X2/5	2.5	50/0.25	25	885	22.00	32
YY34X2/5	2.5	50/0.25	34	1220	25.80	32
YY3X4	4	56/0.30	3	201	10.40	20S
YY4X4	4	56/0.30	4	283	10.70	20S
YY5X4	4	56/0.30	5	293	12.40	20
YY7X4	4	56/0.30	7	413	14.00	25



express electrical

YY3X6	6	84/0.30	3	273	11.50	20
YY4X6	6	84/0.30	4	352	12.80	20
YY5X6	6	84/0.30	5	415	14.60	25
YY7X6	6	84/0.30	7	537	15.20	25
YY3X10	10	80/0.40	3	466	15.30	25
YY4X10	10	80/0.40	4	631	16.50	25
YY5X10	10	80/0.40	5	720	18.60	25
YY3X16	16	126/0.40	3	697	18.40	25
YY4X16	16	126/0.40	4	767	19.90	32
YY5X16	16	126/0.40	5	1151	22.40	32
YY3X25	25	196/0.40	3	930	21.50	32
YY4X25	25	196/0.40	4	1150	22.50	32
YY5X25	25	196/0.40	5	1679	27.90	40
YY4X35	35	276/0.40	4	1970	29.00	40
YY5X35	35	276/0.40	5	2206	31.30	40
YY4X50	50	396/0.40	4	2700	34.00	50S

TYPE YY PVC CABLE – CONDUCTOR RESISTANCE

NOMINAL CROSS SECTIONAL AREA (MM ²)	MAXIMUM DIAMETER OF WIRES IN CONDUCTOR MM	MAXIMUM RESISTANCE CONDUCTOR AT 20°C
0.75	12	26
1	15	19.5
1.5	18	13.3
2.5	26	7.98
4	34	4.95
6	44	3.3
10	61	1.91
16	82	1.21
25	108	0.780
35	135	0.554



express electrical

TYPE YY PVC CABLE – CURRENT CAPACITY

NOMINAL CROSS SECTIONAL AREA (MM ²)	CURRENT CARRY CAPACITY AY 30 ⁰ C IN AIR AMPS	CURRENT CARRY CAPACITY AY 30 ⁰ C IN CONDUIT AMPS
0.75	16	9
1	20	12
1.5	24	15
2.5	32	18
4	42	26
6	54	34
10	73	44
16	98	61

TYPE YY PVC CABLE – VOLTAGE DROP

NOMINAL CROSS SECTIONAL AREA (MM ²)	TWO CORE CABLE DC mV/A/m	SINGLE PHASE TWO CORE CABLE AC mV/A/m	THREE PHASE 3 OR 4 CORE CABLE AC mV/A/m
1	44	44	38
1.5	29	29	25
2.5	18	18	15
4	11	11	9.5
6	7.3	7.3	6.4
10	4.4	4.4	3.8
16	2.8	2.8	2.4